



Mini PTZ Intelligent Vandal Speed Dome

Samsung 10X Zoom Camera and bracket

High resolution, 540TVL Color, 570TVL Black & White

Model: MP10X



Descriptions:

This high quality Aleph America Color Mini Intelligent Vandal Speed Dome Camera is designed for NTSC system. The camera has a wide operation temperature range and is not subject to distortion from magnetic field. With its lightweight and compact size, this camera can be used for monitoring and surveillance.

Protective Cover, Ceiling Mount Bracket Included

Specification:

Model	MP10X (NTSC)
Scanning System	2 : 1 Interlace
Camera components	1/4 In. Interline Transfer CCD
Effective Pixels	NTSC : 768(H) x 494(V)
Scanning Frequency	NTSC : H:15 734 KHz/V:59 94 Hz
Horizontal Resolution	540TV Color , 570TV Black& White
Video Output	Composite Video Signal 1.0Vp-p(75,BNC)
S/N Ratio	50 dB (AGC OFF , Weight ON)
Zoom	10X Optical zoom, 10X Digital zoom
D/N Mode	ICR
Minimum Illumination	Color 0.7Lux/F1.8(50 IRE) , Black & White 0.02Lux/F1.8 (50 IRE)
Privacy Shelter Area	4 areas
White Balance	Auto Tracking White Balance, Auto White Balance Control , Manual
Backlight Compensation	Low , Middle , High , Off
Focus	f=3.8 to 38mm (F 1.8 to 3.2)
Manual Speed	0.5°/sec~360°/sec Adjustable
Preset Speed	Max.360°/sec
Rotation	The level of 360-degree continuous rotation, 180 degrees vertical rotation (electronic flip)
Zoom	Total Zooms : 100X (10X Optical zoom , 10X Digital zoom)
Preset Position	127EA
Pattern scanning	4 Teams
Line scanning	8 lines
Group Cruise	8 Teams (Each group of 20 preset functions)
Remote Control	RS-485 (Pelco D , P Protocol)
Screen	English Menu
Alarm Input (Optional)	4 lines
Operational Temperature	-10°C to +50°C / 14°F to 122°F
Humidity	Within 90%RH
Operational Voltage	DC12V / 1A
Weight	About 4.189 lbs (Without Bracket)
Dimensions (D×H) inches	5" ½ Diameter 5" tall (Without Bracket)

*Specifications are subject to change without prior notice.

- Input voltage exceeding the nominal rating by over +/-10% will cause abnormal operation.